according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 14 Feb 2025 **Print date:** 18 Feb 2025

Version: 1 Page 1/11



Paint Killer_ Lackentferner

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Paint Killer Lackentferner

Article No.:

500908113

UFI:

C300-P0FR-F00W-GPE0

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Farbentfernung von lackierten Modellen

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Tamiya-Carson Modellbau GmbH & Co. KG

Werkstraße 1 90765 Fürth Germany

Telephone: +49 911 9765 03 Telefax: +49 911 9765 285 E-mail: info@tamiya-carson.de Website: www.tamiya.de

1.4. Emergency telephone number

No data available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (Flam. Liq. 2)	H225: Highly flammable liquid and vapour.	On basis of test data.
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	Calculation method.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:



GHS02 Flame



GHS07 Exclamation mark

Signal word: Danger

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 14 Feb 2025 **Print date:** 18 Feb 2025

Version: 1 Page 2/11



Paint Killer_Lackentferner

Hazard components for labelling:

1-methoxypropan-2-ol; ethyl acetate

Hazard statements for physical hazards	
H225	Highly flammable liquid and vapour.

Hazard statements for health hazards	
H336	May cause drowsiness or dizziness.

Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.

Precautionary statements		
P101 If medical advice is needed, have product container or label at hand.		
P102	P102 Keep out of reach of children.	
P103	Read carefully and follow all instructions.	

Precautionary statements Prevention		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P261	Avoid breathing vapours and spray.	
P271	Use only outdoors or in a well-ventilated area.	
P280	Wear eye protection/face protection.	

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name	Concentration
	Classification according to Regulation (EC) No 1272/2008 [CLP]	
CAS No.: 107-98-2 EC No.: 203-539-1 Index No.: 603-064-00-3	1-methoxypropan-2-ol Flam. Liq. 3 (H226), STOT SE 3 (H336) Warning Acute Toxicity Estimate ATE (oral) 3,739 mg/kg ATE (dermal) > 2,000 mg/kg	54 – < 95 weight-%
CAS No.: 141-78-6 EC No.: 205-500-4 Index No.: 607-022-00-5 REACH No.: 01-2119475103-46-XXXX	ethyl acetate Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger EUH066 Acute Toxicity Estimate ATE (dermal) > 20,000 mg/kg ATE (inhalation, vapour) > 22.5 mg/L	5 - ≤ 9.99 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended.

Following inhalation:

Provide fresh air. In case of respiratory tract irritation, consult a physician. Get medical advice/attention if you feel unwell.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 14 Feb 2025 Print date: 18 Feb 2025

Version: 1 Page 3/11



Paint Killer_ Lackentferner

Following ingestion:

Rinse mouth. Let 1 glass of water be drunken in little sips (dilution effect). Get medical advice/attention if you feel unwell.

Self-protection of the first aider:

Use personal protection equipment.

4.2. Most important symptoms and effects, both acute and delayed

Dizziness Dizziness

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water spray jet alcohol resistant foam Extinguishing powder Carbon dioxide (CO2)

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

Combustible

Hazardous combustion products:

Thermal decomposition Carbon monoxide In case of fire: Gases/vapours, toxic.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Remove persons to safety.

Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Provide adequate ventilation.

For cleaning up:

Do not rinse down with water.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

6.5. Additional information

Use appropriate container to avoid environmental contamination.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 14 Feb 2025 **Print date:** 18 Feb 2025

Version: 1 Page 4/11



Paint Killer Lackentferner

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Wear personal protection equipment (refer to section 8).

Fire prevent measures:

Keep away from sources of ignition - No smoking.

Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

Storage class (TRGS 510, Germany): 3 - Flammable liquids

7.3. Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
IOELV (EU)	1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	 100 ppm (375 mg/m³) 150 ppm (568 mg/m³) (may be absorbed through the skin)
WEL (GB)	1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	 ① 100 ppm (375 mg/m³) ② 150 ppm (560 mg/m³) ⑤ (may be absorbed through the skin)
WEL (GB) from 21 Aug 2018	ethyl acetate CAS No.: 141-78-6 EC No.: 205-500-4	① 200 ppm (734 mg/m³) ② 400 ppm (1,468 mg/m³)
IOELV (EU) from 21 Feb 2017	ethyl acetate CAS No.: 141-78-6 EC No.: 205-500-4	① 200 ppm (734 mg/m³) ② 400 ppm (1,468 mg/m³)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	PNEC Value	① PNEC type
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	10 mg/L	① PNEC aquatic, freshwater
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	100 mg/L	① PNEC aquatic, marine water
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	100 mg/L	① PNEC sewage treatment plant

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 14 Feb 2025 **Print date:** 18 Feb 2025

Version: 1 Page 5/11



Paint Killer Lackentferner

Substance name	PNEC Value	① PNEC type
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	52.3 mg/kg	① PNEC sediment, freshwater
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	5.2 mg/kg	① PNEC sediment, marine water
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	4.59 mg/kg	① PNEC soil
ethyl acetate CAS No.: 141-78-6 EC No.: 205-500-4	240 μg/L	① PNEC aquatic, freshwater
ethyl acetate CAS No.: 141-78-6 EC No.: 205-500-4	24 μg/L	① PNEC aquatic, marine water
ethyl acetate CAS No.: 141-78-6 EC No.: 205-500-4	650 mg/L	① PNEC sewage treatment plant
ethyl acetate CAS No.: 141-78-6 EC No.: 205-500-4	1.15 mg/kg	① PNEC sediment, freshwater
ethyl acetate CAS No.: 141-78-6 EC No.: 205-500-4	0.115 mg/kg	① PNEC sediment, marine water
ethyl acetate CAS No.: 141-78-6 EC No.: 205-500-4	0.148 mg/kg	① PNEC soil
ethyl acetate CAS No.: 141-78-6 EC No.: 205-500-4	200 mg/kg	① PNEC secondary poisoning

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Wash hands before breaks and after work.

8.2.2. Personal protection equipment

Eye/face protection:

Use tightly fitting protective goggles

Skin protection:

Wearing time with occasional contact (splashes): Tested protective gloves must be worn EN ISO 374 Suitable material:NBR (Nitrile rubber) Thickness of the glove material 0,4 Breakthrough time: >30 min. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. In the case of wanting to use the gloves again, clean them before taking off and air them well. Breakthrough times and swelling properties of the material must be taken into consideration.

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Respiratory protection necessary at: aerosol or mist formation

8.2.3. Environmental exposure controls

Discharge into the environment must be avoided. Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid Colour: colourless
Odour: Turpentine flammability: Yes

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 14 Feb 2025 **Print date:** 18 Feb 2025

Version: 1 Page 6/11



Paint Killer_ Lackentferner

Safety relevant basis data

Parameter	Value	at °C	① Method
			② Remark
рН	No data available		
Melting point	No data available		
Freezing point	No data available		
Initial boiling point and boiling range	77 °C		② Pre-supplier/manufacturer
Flash point	-1 °C		② Pre-supplier/manufacturer
Evaporation rate	No data available		
Auto-ignition temperature	No data available		
Upper/lower flammability or explosive limits	2.1 - 11.5 Vol-%		② Pre-supplier/manufacturer
Vapour pressure	No data available		
Vapour density	No data available		
Density	0.92 g/mL	20 °C	② Pre-supplier/manufacturer
Bulk density	not applicable		
Water solubility	No data available		
Dynamic viscosity	No data available		
Kinematic viscosity	No data available		

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Avoid high temperatures or direct sunlight.

10.5. Incompatible materials

Oxidising agent, strong Oxidising agent, strong

10.6. Hazardous decomposition products

Decomposition products in case of fire: see section 5.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1

LD₅₀ oral: 3,739 mg/kg (rat) EU Method B.1 (Acute Toxicity (Oral))

LD₅₀ dermal: >2,000 mg/kg (rat) EU Method B.3 (Acute Toxicity (Dermal))

ethyl acetate CAS No.: 141-78-6 EC No.: 205-500-4

LD₅₀ dermal: >20,000 mg/kg (rabbit)

LC₅₀ Acute inhalation toxicity (vapour): >22.5 mg/L 6 h (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 14 Feb 2025 Print date: 18 Feb 2025

Version: 1 Page 7/11



Paint Killer_ Lackentferner

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Additional information:

No data available

11.2. Information on other hazards

No data available

SECTION 12: Ecological information

12.1. Toxicity

1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1

LC₅₀: ≥1,000 mg/L 4 d (fish, Oncorhynchus mykiss (previous name: Salmo gairdneri)) OECD Guideline 203 (Fish, Acute Toxicity Test)

LC₅₀: 21,100 – 25,900 mg/L 2 d (crustaceans, Daphnia magna) Environmental Sciences Research Test Method No. ESR-ES-15

EC₅₀: >1,000 mg/L 7 d (Algae/water plant, Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)) Test method ET-11-1987-1. Algal toxicity test.

NOEC: ≥1,000 mg/L 4 d (fish, Oncorhynchus mykiss (previous name: Salmo gairdneri)) OECD Guideline 203 (Fish, Acute Toxicity Test)

ethyl acetate CAS No.: 141-78-6 EC No.: 205-500-4

LC₅₀: 220 mg/L 4 d (Pimephales promelas)

LC₅₀: 230 mg/L 4 d (fish, Pimephales promelas) US EPA method E03-05

EC₅₀: 164 mg/L 2 d (Daphnia)

EC₅₀: 5,600 mg/L 2 d (Algae/water plant, Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)) DIN 38 412, Part 9 (draft standard)

EC₅₀: 220 mg/L 4 d (fish, Pimephales promelas) US EPA method E03-05

NOEC: 2.4 mg/L 21 d (crustaceans, Daphnia magna) OECD 211

NOEC: >100 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)) OECD Guideline 201 (Alga, Growth Inhibition Test)

NOEC: 2.4 mg/L 21 d (crustaceans, Daphnia magna)

IC₅₀: 346 mg/L 1 d (crustaceans, Artemia salina)

LC₅₀: 230 mg/L 4 d (fish, Pimephales promelas)

12.2. Persistence and degradability

1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1

Biodegradation: Yes, rapidly

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 14 Feb 2025 **Print date:** 18 Feb 2025

Version: 1 Page 8/11



Paint Killer_ Lackentferner

ethyl acetate CAS No.: 141-78-6 EC No.: 205-500-4

Biodegradation: Yes, rapidly

12.3. Bioaccumulative potential

1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1

 $\textbf{Log K}_{\textbf{OW}}\textbf{:}<1$

ethyl acetate CAS No.: 141-78-6 EC No.: 205-500-4

Log K_{OW}: 0.86

Bioconcentration factor (BCF): 30 Species: Leuciscus idus melanotus

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

ethyl acetate CAS No.: 141-78-6 EC No.: 205-500-4

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Endocrine disrupting properties

No known symptoms to date.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

	20 01 13 *	(20) MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND		
١		INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS		
١		(01) separately collected fractions (except 15 01)		
		(13 *) Solvents		

^{*:} Evidence for disposal must be provided.

Directive 2008/98/EC (Waste Framework Directive)

HP 3	Flammable
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Waste code packaging

15 01 10 *	(15) WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING
	NOT OTHERWISE SPECIFIED
	(01) packaging (including separately collected municipal packaging waste)
	(10 *) packaging containing residues of or contaminated by dangerous substances

^{*:} Evidence for disposal must be provided.

Waste treatment options

Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 1263	UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name			
PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 14 Feb 2025 Print date: 18 Feb 2025

Version: 1 Page 9/11



Paint Killer_ Lackentferner

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.3. Transport haza	ard class(es)		,
*	· ·		
3	3	3	3
14.4. Packing group			
II	II	II	II
14.5. Environmental	hazards	*	
No	No	No	No
14.6. Special precau	tions for user	-	
Special Provisions: 163 367 640D 650	Special Provisions: 163 367 640D 650	Special Provisions: 163 367	Special Provisions: A3 A72 A192
Limited quantity (LQ): 5 L	Limited quantity (LQ): 5 L	Limited quantity (LQ): 5 L	Limited quantity (LQ): Y341
Excepted Quantities (EQ): E2	Excepted Quantities (EQ):	Excepted Quantities (EQ):	Excepted Quantities (EQ):
Hazard identification number (Kemler No.): 33	Classification code: F1	EmS-No.: F-E, S-E	
Classification code: F1			
Tunnel restriction code: (D/E)			

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

Contains no REACH Annex XIV substances. Contains no substance on the REACH candidate list. The mixture has not been subjected to a safety assessment

Other regulations (EU):

Hazard categories:

- P5a Flammable Liquids, Category 1 or 2
- P5b Flammable liquids
- P5c Flammable liquids of Categories 2 or 3, not covered by P5a and P5b

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 100 weight-%

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

The mixture has not been subjected to a safety assessment.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 14 Feb 2025 Print date: 18 Feb 2025

Version: 1 Page 10/11



Paint Killer_ Lackentferner

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

ACGIH American Conference of Governmental Industrial Hygienists

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland

Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

BCF Bioconcentration Factor CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging

DIN German Institute for Standardization / German Industrial Standard

DNEL derived no-effect level EC₅₀ Effective Concentration 50%

EN European Standard ES Exposure scenario

EWC European Waste Catalogue IC₅₀ Inhibition Concentration 50 %

ICAO International Civil Aviation Organization
 IMDG International Maritime Dangerous Goods
 IMO International Maritime Organization
 ISO International Standards Organisation

KG body weight

LC₅₀ Lethal (fatal) Concentration 50%

LD₅₀ Lethal (fatal) Dose 50%

MAK Maximum concentration in the workplace air (CH)

NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety & Health

NOEC No Observed Effect Concentration

OECD Organisation for Economic Cooperation and Development

OSHA Occupational Safety & Health Administration PBT persistent and bioaccumulative and toxic

PNEC Predicted No Effect Concentration

REACH Registration, Evaluation and Authorization of Chemicals RID Dangerous goods regulations for transport by rail

TRGS Technische Regeln für Gefahrstoffe

UN United Nations

VOC Volatile organic compounds

16.3. Key literature references and sources for data

Substance name	Туре	source of supply
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	LD_{50} oral; LD_{50} dermal; LC_{50} ; EC_{50} ; $NOEC$	Source: European Chemicals Agency, http://echa.europa.eu/
ethyl acetate CAS No.: 141-78-6 EC No.: 205-500-4	LD_{50} dermal; LC_{50} ; EC_{50} ; NOEC; IC_{50}	Source: European Chemicals Agency, http://echa.europa.eu/

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (Flam. Liq. 2)	H225: Highly flammable liquid and vapour.	On basis of test data.
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	Calculation method.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 14 Feb 2025 **Print date:** 18 Feb 2025

Version: 1 Page 11/11



Paint Killer_ Lackentferner

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.

16.6. Training advice

No data available

16.7. Additional information

No data available